



UR SERIES - ULTRA REDUCTION

Tip Cap	PSI	Drop Size	Capacity One Nozzle (GPM)	20" Spacing							
				GPA							
				5 MPH	6 MPH	7.5MPH	10 MPH	12.5 MPH	15 MPH	17.5 MPH	20MPH
UR110-04 (50)	20										
	30	UC	0.35	21.0	17.3	13.7	10.3	8.2	6.9	5.9	5.1
	40	UC	0.4	24.0	19.8	15.8	11.9	9.5	7.9	6.8	5.9
	50	UC	0.45	27.0	22.3	17.7	13.3	10.6	8.9	7.6	6.6
	60	UC	0.49	29.0	24.3	19.4	14.5	11.6	9.7	8.3	7.3
	70	UC	0.53	31.0	26.2	21.0	15.7	12.6	10.5	9.0	7.9
UR110-05 (50)	20										
	30	UC	0.43	26.0	21.3	17.1	12.9	10.3	8.6	7.3	6.4
	40	UC	0.5	30.0	24.8	20.0	15.0	11.9	9.9	8.5	7.4
	50	UC	0.56	33.0	27.7	22.0	17.0	13.3	11.1	9.5	8.3
	60	UC	0.61	36.0	30.2	24.0	18.0	14.5	12.1	10.4	9.1
	70	UC	0.66	39.0	32.7	26.0	20.0	15.7	13.1	11.2	9.8
UR110-06 (50)	20										
	30	UC	0.52	31.0	25.8	20.6	15.4	12.3	10.3	8.8	7.7
	40	UC	0.6	36.0	29.7	23.8	17.8	14.3	11.9	10.2	8.9
	50	UC	0.67	40.0	33.2	27.0	20.0	15.9	13.3	11.4	10.0
	60	UC	0.73	44.0	36.0	29.0	22.0	17.5	14.5	12.5	10.9
	70	UC	0.79	47.0	39.0	31.0	24.0	19.0	15.7	13.5	11.8
UR110-08	20										
	30	UC	0.69	41.0	34.0	27.0	21.0	16.0	14.0	12.0	10.0
	40	UC	0.8	48.0	40.0	32.0	24.0	19.0	16.0	14.0	12.0
	50	UC	0.89	53.0	44.0	35.0	27.0	21.0	18.0	15.0	13.0
	60	UC	0.98	58.0	49.0	39.0	29.0	23.0	19.0	17.0	15.0
	70	UC	1.06	63.0	53.0	42.0	31.0	25.0	21.0	18.0	16.0
UR110-10	20										
	30	UC	0.87	51.0	43.0	34.0	26.0	21.0	17.0	15.0	13.0
	40	UC	1	59.0	50.0	40.0	30.0	24.0	20.0	17.0	15.0
	50	UC	1.12	66.0	56.0	44.0	33.0	27.0	22.0	19.0	17.0
	60	UC	1.22	73.0	60.0	48.0	36.0	29.0	24.0	21.0	18.0
	70	UC	1.32	79.0	65.0	52.0	39.0	31.0	26.0	22.0	20.0



UR SERIES - ULTRA REDUCTION

DROPLET SIZE - ULTRA COARSE

COVERAGE - FAIR

DRIFT POTENTIAL - LEAST LIKELY TO DRIFT

DESIGN - DUAL ORIFICE FLAT FAN

